



ATTESTATION

of conformity with UK legislation

BV LCIE CHINA Number N°2266AS08ASCQ46224
Product EV Charging Station
Reference See model list
Issued to Zhejiang Etek Electrical Technology Co.,Ltd.
Address No.288 Wei 17th Road , Yueqing Economic Development Zone
Yueqing, Wenzhou, Zhejiang Province P.R.China
Manufacturer Zhejiang ETEK Electrical Technology Co.,Ltd.
Technical characteristics See model list

The submitted sample of the above equipment has been tested for the below regulation(s):
-Radio Equipment Regulations 2017

<i>Standards</i>	<i>Report number</i>	<i>Report date</i>
BS EN IEC 61851-1:2019	ASCQ-ESH-P22041244-U	Aug 16th, 2022
Article 3.1(a) Health: BS EN 50663:2017 BS EN 62479:2010	ASCQ-ESH-P22041244B-2	Aug 16th, 2022
Article 3.1(b) EMC: ETSI EN 301 489-1 V2.2.3 (2019-11) ETSI EN 301 489-3 V2.1.1 (2019-03)	ASCQ-ESH-P22041244B-1	Aug 16th, 2022
Article 3.2 Radio: ETSI EN 300 330 V2.1.1 (2017-02)	ASCQ-ESH-P22041244B-3	Aug 16th, 2022

The referred test report(s) show that the product complies with standard(s) recognized as giving presumption of compliance with the essential requirement covered by the regulations

This verification does not imply assessment of the production of the product

The UKCA marking may be affixed on the product if all relevant UK legislations are fulfilled

Shanghai (P.R. China), August 19th, 2022

Denis SUN

Product Line Manager





**BUREAU
VERITAS**

This document shall not be reproduced, except in full, without the written approval of BV LCIE China. Information given in this document, are related to the tested specimen of the described electrical sample.

Version: 7.0 / Feb.10, 2021

Page 2 of 2

Model list

Model name	Rated voltage/Hz	Rated current	Connection method	IP	Weight
EKEC4-C-T2-1P-16A-M-E	AC 240V \pm 10% 50Hz	Max 16A	Case C	54	3,8 kg
EKEC4-C-T2-1P-32A-M-E	AC 240V \pm 10% 50Hz	Max 32A	Case C	54	4,0 kg
EKEC4-C-T2-3P-16A-M-E	AC 420V \pm 10% 50Hz	Max 16A	Case C	54	4,0 kg
EKEC4-C-T2-3P-32A-M-E	AC 420V \pm 10% 50Hz	Max 32A	Case C	54	4,5 kg
EKEC4-S-T2-1P-16A-M-E	AC 240V \pm 10% 50Hz	Max 16A	Case B	54	2,3 kg
EKEC4-S-T2-1P-32A-M-E	AC 240V \pm 10% 50Hz	Max 32A	Case B	54	2,5 kg
EKEC4-S-T2-3P-16A-M-E	AC 420V \pm 10% 50Hz	Max 16A	Case B	54	2,5 kg
EKEC4-S-T2-3P-32A-M-E	AC 420V \pm 10% 50Hz	Max 32A	Case B	54	2,8 kg
EKEC4-C-T2-1P-16A-PEN	AC 240V \pm 10% 50Hz	Max 16A	Case C	54	4.5 kg
EKEC4-C-T2-1P-32A-PEN	AC 240V \pm 10% 50Hz	Max 32A	Case C	54	4.8 kg
EKEC4-S-T2-1P-16A-PEN	AC 240V \pm 10% 50Hz	Max 16A	Case B	54	2.8 kg
EKEC4-S-T2-1P-32A-PEN	AC 240V \pm 10% 50Hz	Max 32A	Case B	54	2.9 kg

NOTE: Operation temperature: -25°C— 40°C ;
Rated frequency: 50Hz.